

# S-ZP SERIES

## High rigidity pad (ø32 ~ ø340)

### How to order



High Rigidity Pad

S-ZP

② Pad Diameter  
40

③ Pad Form  
H

④ Pad Material  
N

③ Pad Type	② Pad Diameter (mm)											④ Pad Material		
	H*	P*	J*	K*	M*	N†	O†	N	S					
○	32	40	50	63	80	100	125	150	200	250	300	340	N	NBR
☆	ø32	ø40	ø50	ø63	ø80	ø100	ø125	ø150	ø200	ø250	ø300	ø340	S	Silicone
H	Flat type with ribs	●	●	●	●	●	●	●	●	●	●	●		
HB	Bellows type	●	●	●	●	●	●	●	-	-	-	-		

### Dimension

(mm)

High rigidity pad								
<b>H Flat type with ribs 32</b>								
Model	Weight (g)							
S-ZP32H	7.2							
<b>H Flat type with ribs 40,50</b>								
Model	øA	øB	øC	Weight (g)				
S-ZP40H	40	42	32	14.2				
S-ZP50H	50	52	42	27				
<b>H Flat type with ribs 63,80</b>								
Model	øA	øB	øC	P	Y	Weight (g)		
S-ZP63H	63	65	50	14.5	3.5	52		
S-ZP80H	80	82	61	16.5	4.5	80		
<b>H Flat type with ribs 100,125</b>								
Model	øA	øB	øC	Weight (g)				
S-ZP100H	100	103	80	177				
S-ZP125H	125	128	104	310				
<b>H Flat type with ribs 150,200</b>								
Model	øA	øB	øC	D	øE	P	Y	Weight (g)
S-ZP150H	150	155	103	8	14	33	7	355
S-ZP200H	200	205	140	11	12	36	13	542
<b>H Flat type with ribs 250</b>								
Model	Weight (g)							
S-ZP250H	835							
<b>H Flat type with ribs 300,340</b>								
Model	Weight (g)							
S-ZP300H	2117							
Model	Weight (g)							
S-ZP340H	2630							